

MODEL DD45P





WORRY-FREE PUMP FUNCTION

THE PATENTED PUMP FUNCTION ALLOWS THE UNIT TO CONTINUOUSLY DISCHARGE MOISTURE VITHOUT CONSTANTLY EMPTYING A BUCKET. THE UNIT CAN PUMP WATER UPWARD TO DRAIN OUT A BASEMENT WINDOW OR INTO A SINK, UP TO 16' WITH THE PROVIDED HOSE.



LCD ELECTRONIC CONTROLS

CHOOSE THE IDEAL HUMIDITY LEVEL BY
ADJUSTING THE HUMIDISTAT. THE
ELECTRONIC CONTROLS ALLOW YOU TO
MONITOR RELATIVE HUMIDITY AND
TEMPERATURE.



VISIBLE WATER LEVEL

WITH ITS FRONTALLY LOCATED TANK AND TRANSPARENT WATER LEVEL WINDOW, YOU CAN EASILY SEE HOW MUCH WATER HAS BEEN COLLECTED.



SAP: 01	4884020	2		D D 45F		
UPC: 0-	44387-01	1045-0				
SCC14:			W	attage:	tage:	
	W	D	Н	Lbs		
Unit	14.96	11.81	24.02	41.23		
VOL Unit ft3:		2.46				
Carton:	16.54	13.98	27.17	47.84		
VOL Carton ft3:		3.63				
Pcs per Mast	er:	0				
Master:	0.00	0.00	0.00	0.00		
VOL Master f	t3:	0.00				
Container:	20'	40'	40HC'	45'		
	255	534	534	0		
Factory code:	NIMT					

EMPTY THE COLLECTED WATER 3 WAYS:

- CONTINUOUSLY THROUGH **PATENTED PUMP SYSTEM**: [16 FT HOSE INCLUDED]
- Passively through the 3' hose [included]
- DIRECTLY INTO THE TANK [7.0 LITER CAPACITY]

ELECTRONIC CLIMATE CONTROL WITH LCD DISPLAY:

- ADJUSTABLE HUMIDISTAT
- ROOM THERMOSTAT
- 24-H TIMER
- ANTI-FROST DEVICE (DOWN TO 41°F)
- FAN SPEED CONTROL 2 FAN SPEEDS

TANK CONTROL SYSTEM WITH ALARM

CAN BE EASILY MOVED BY CASTOR WHEELS AND HANDLES



R410A REFRIGERANT GAS

UPDATED: 11/24/09

DISCLAIMER: FEATURES AND COLORS ARE TENTATIVE AND SUBJECT TO CHANGE WITHOUT NOTICE.